

NOTAS TÉCNICAS TECHNICAL NOTES

Medir Size	120/150/180 cm
Acabado Finish	Acero inoxidable satinado Stainless steel satin Acero inoxidable pintado Stainless steel painted ¹
Comandi Controls	Electrónicos 3 V+I Electronic 3 S+I
Iluminación Lighting	Lámparas led Led lamps 2x2,5 W - 3000 K (120) 3x2,5 W - 3000 K (150/180)

PERFORMANCE PERFORMANCE

Capacidad Airflow (m ³ /h)	750
Presión Pressure (Pa)	580
Ruido Noise level (Lw[dBA])	46 min - 64 max
Potencia del motor Motor power (W)	275
Capacidad del motor Motor airflow (m ³ /h)	800
Versión Version	Aspirante/Filtrado (opcional) Suction/Filtering (optional)
Salida Duct size (mm)	Ø 150/Ø 120
Clase de energía Energy class	A

ACCESORIOS ACCESSORIES

Kit de filtro Filtering kit
Filtro de carbón rectangular
Rectangular charcoal filters

CÓDIGO CODE

K0700KIT
55046266

MODELO MODEL

14-120/INOX
14-150/INOX
14-180/INOX
14-120/COLOR
14-150/COLOR
14-180/COLOR

CÓDIGO CODE

K0014120EXL
K0014150EXL
K0014180EXL
K0014120ECL
K0014150ECL
K0014180ECL

¹ Coloraciones estándar (ver Coloraciones) o personalizados bajo pedido
Standard colors (see Colors) or custom on request

Kit de filtro: deflector, tubo extensible, pinzas metálicas, filtro de carbón
Filtering kit: deflector, extendable hose, clamps metal, charcoal filter

Modelo compatible con motores remotos (ver Motores remotos)
Models suitable for remote motors (see Remote motors)

