

95 i



NOTAS TÉCNICAS TECHNICAL NOTES

Medir Size	90/120 cm - H 60/100 cm
Acabado Finish	Acero inoxidable satinado Stainless steel satin Acero inoxidable pintado Stainless steel painted ¹
Comandí Controls	Electrónicos 3 V+, Mando a distancia Electronic 3 S+, Remote control
Iluminación Lighting	Lámparas led Led lamps 4x2,2 W - 3000 K

PERFORMANCE PERFORMANCE

Capacidad Airflow (m ³ /h)	790
Presión Pressure (Pa)	605
Ruido Noise level (Lw[dBA])	42 min - 64 max
Potencia del motor Motor power (W)	275
Capacidad del motor Motor airflow (m ³ /h)	820
Versión Version	Aspirante/Filtrado (opcional) Suction/Filtering (optional)
Salida Duct size (mm)	Ø 150/Ø 120
Clase de energía Energy class	A+

ACCESORIOS ACCESSORIES

Kit de filtro Filtering kit	K90095090KIT (90) K90095120KIT (120) 55046757
Par de filtro de carbón redondo Pair circular charcoal filter	

MODELO MODEL

95-90 i/INOX	K0095090EXIL-1
95-120 i/INOX	K0095120EXIL-1
95-90 i/COLOR	K0095090ECIL-1
95-120 i/COLOR	K0095120ECIL-1

¹ Coloraciones estándar (ver Coloraciones) o personalizados bajo pedido
Standard colors (see Colors) or custom on request

Kit de filtro: deflector, tubo extensible, pinzas metálicas, filtro de carbón
Filtering kit: deflector, extendable hose, clamps metal, charcoal filter

Modelo compatible con motores remotos (ver Motores remotos) Models suitable for remote motors (see Remote motors)

